

6070-200 Stripping Powder

Technical Data Sheet

Page 1/1

Stripping Powder is ideal for reclaiming of polymer-based direct photo emulsions and capillary films such as Diazo and SBQ-sensitized emulsions. It can be used on all types of mesh. The property of the reclaimer solution can be adjusted more or less water to dissolve the powder.

Physical Data:

Colour: White
Consistency: Powder
Shelf Life: 1 year at 20°C, 68°F

application

Mixing:
Dilute Stripping Powder as follows:

- 100 grams : 10 litres of water – for normal decoating
- 100 grams : 5 litres of water – for decoating old stencils or used for long print runs or treated with chemical hardener

1. Soak the screen with water.
2. Apply a small quantity of Stripping Powder using a soft brush or sponge to both sides of the mesh, rubbing in a circular motion. Ensure that it is distributed equally over the screen.
3. Let it stand for 2-3 minutes to dissolve emulsion coating but do not allow Stripping Powder to dry onto the screen as this will make stencil difficult to remove.
4. Rinse the screen with strong water spray in vertical position. Rinse well until the water runs off without any foaming.
5. Dry as usual prior to applying stencils.

Handling and Storage

- It is recommended to wear suitable protective goggles and gloves. Take particular care to avoid splashes into the eyes and skin contact. If this does occur, rinse immediately with plenty of water. In case of splashes into the eyes, seek medical advice.
- Comprehensive information on the safety and handling of Stripping Powder 6070-200 is given in the appropriate Smiley Material Safety Data Sheet (MSDS), which are available upon request.
- Stripping Powder should be stored in a cool dry area away from heat, light and organic matters (food drinks, etc.). Containers should be tightly closed immediately after use.

Environmental Information

This product is not considered hazardous in general. The working solution can generally be emptied into the drains however larger quantities should be disposed of according to local regulations.

Additional Information

For additional product information, please visit our website at www.smiley.co.th. For further information, please contact SPS personnel at CRM@smiley.co.th.

Thank you for choosing SMILEY.

Product Offering:

Packaging: 6070-200 is available in 1 kilo, 5 kilos and 20 kilos containers.